

**CALCULATIONS OF RADIATIVE HEAT TRANSFER IN AN AXISYMMETRIC JET  
DIFFUSION FLAME AT ELEVATED PRESSURES USING DIFFERENT METHODS**

**H. Chu<sup>1</sup>, J.-L. Consalvi<sup>2</sup>, M. Gu<sup>1</sup> and F. Liu<sup>3</sup>**

<sup>1</sup>School of Energy and Environment, Anhui University of Technology,  
Ma'anshan 243002, China

<sup>2</sup>Aix-Marseille Université, IUSTI/ UMR CNRS 7343, 5 rue E. Fermi, 13453  
Marseille Cedex 13, France

<sup>3</sup>Measurement Science and Standards, National Research Council, Ottawa, Ontario, Canada

**ABSTRACT.** Radiation heat transfer in axisymmetric jet diffusion flames under conditions relevant to oxygen-enriched combustion at total pressures of 1 and 30 atm was calculated using several gas radiation models: line-by-line, narrow-band correlated-k, wide-band correlated-k, full-spectrum correlated-k, and weight-sum-of-grey-gases. An optimized full-spectrum correlated-k, an optimized narrow-band correlated-k, and a wide-band correlated-k model were proposed and evaluated. Line-by-line results are used as the benchmark solution in the evaluation of other gas radiation models. The optimized full-spectrum correlated-k model was found to improve significantly the computational efficiency to a level comparable to that of the weight-sum-of-gray-gases model without significant loss of accuracy.