

**CALCULATIONS OF THERMAL RADIATION TRANSFER OF C<sub>2</sub>H<sub>2</sub> AND C<sub>2</sub>H<sub>4</sub>  
TOGETHER WITH H<sub>2</sub>O, CO<sub>2</sub>, AND CO IN A ONE-DIMENSIONAL ENCLOSURE  
USING LBL AND SNB MODELS**

**Chaobo Qi, Shu Zheng and Huaichun Zhou**

Department of Thermal Engineering, Tsinghua University Beijing 100084, China

**ABSTRACT.** The Statistical Narrow-Band model parameters for C<sub>2</sub>H<sub>2</sub> and C<sub>2</sub>H<sub>4</sub> are generated. The distributions of the concentrations of radiating gases and the temperature along the centerline of a laminar ethylene/air diffusion flame were chosen to be tested. Thermal radiation transfer in the one-dimensional planar enclosure was calculated using the line-by-line model and the Statistical Narrow-Band model, and the results of these two models show good agreements. Below the height of 1.8 cm, the average fraction contributed by C<sub>2</sub>H<sub>2</sub> and C<sub>2</sub>H<sub>4</sub> in the radiative heat source is 38.6%, while that by CO is only 5.5%. This result indicates that the involvement of C<sub>2</sub>H<sub>2</sub> and C<sub>2</sub>H<sub>4</sub> in radiation heat transfer should be taken into account in the numerical modelling of the ethylene/air diffusion flame, especially in the early stage of combustion.